

OPEX[®] OMATION[®] SERIES 410

Mail Opener with Built-in Printing
and Sequencing Capabilities



WHY SERIES 410™ ENVELOPENER®?

The OMATIION® Series 410™ Envelopener® offers the performance and features found in a high-end envelope opener but is ideal for mid-sized incoming mail operations.

With the addition of an inkjet printer and a 5.5" operator screen, the Series 410 offers supreme functionality and optimised efficiency. Perfect for operations that process between 200 and 2000 pieces of mixed mail per day, the Series 410's self-adjusting feeder and adjustable cut depth settings enable mixed mail thicknesses and sizes to be fully opened edge-to-edge.

FEATURES

SPECIALISED CUTTING TECHNOLOGY

The milling cutter opens the envelope from edge-to-edge while minimising cut contents and provides a soft, feathered edge which greatly reduces the risk of painful paper cuts.

INKJET PRINTER

Companies and government agencies that require date and time audit trails as well as a unique sequence number for traceable mail, can accomplish both with one device.

USER-FRIENDLY DISPLAY

A 5.5" display provides access to job functions, settings and counting. Simple navigation allows operators to quickly and easily select one of eight preset jobs.

CUT DEPTH ADJUSTMENT KNOB

The cut depth adjustment knob has three optimal cut-depth settings to accommodate various mail types, including thin airmail envelopes, thick envelopes, and overnight envelopes. The no-cut setting is a fast and accurate way to count envelopes, including ballots.

ADVANTAGES

UNMATCHED CUTTING

A soft feathered edge minimises painful papercuts while providing edge-to-edge opening for ease of content extraction without using razors.

SECURE ENVELOPE TRACKING

Date and time stamp, as well as sequencing capabilities are built into the OMATIION Series 410 Envelopener, offering businesses a secure way to sort, open and track incoming mail.

SMALL FOOTPRINT

Since opening and printing are on one piece of equipment, the OMATIION Series 410 Envelopener can easily fit on a desktop.

ELIMINATE WASTE

The milling cutter "chips" away the edge of the envelope and waste is channeled into a large capacity chip bin that can be easily emptied.

SPECIFICATIONS

BASIC SYSTEM CONFIGURATION

Length	40.3 in (1023.6 mm)
Depth	16.5" (419.1mm) or 18" (457.2mm) with power cord
Height	14.3" (363.2mm)
Weight	55 lbs (24.94 kg)

PERFORMANCE CHARACTERISTICS

Speed	Up to 400 envelopes per minute (6" envelope)
Envelope Sizes and Types	All sizes and types (including overnight envelopes)
Thickness	Up to .188 in (4.8 mm) envelope thickness Up to .188" (4.8mm)
Depth of Cut	From .01"-.07" (.25mm - 1.79mm)
Electrical Requirements	1964 BTU/h (max @ 115v/5A) 110-120 VAC, 60Hz, 5A
Decibel Rating	Does not exceed safety standard of 80 dB.

Have questions?

Contact us.

 opex.com

 info@opex.com

OPEX[®]